

BOSCH ORBITAL SANDERS

PSS 200 A

Sanding surface

Sanding plate, width: 93 mm

Sanding plate, length: 185 mm

Sanding surface: 167 cm²

Sanding sheet with Velcro-type fastening, width: 93 mm

Sanding sheet with Velcro-type fastening, length: 185 mm

Technical data

Rated power input: 200 W

Orbital stroke rate when idling: 24.000 1/min

Oscillating circuit diameter: 2,0 mm

Weight: 1,6 kg



PSS 250 AE

Sanding surface

Sanding plate, width: 93 mm

Sanding plate, length: 185 mm

Sanding surface: 167 cm²

Sanding sheet for clamping, width: 93 mm

Sanding sheet for clamping, length: 230 mm

Sanding sheet with Velcro-type fastening, width: 93 mm

Sanding sheet with Velcro-type fastening, length: 185 mm

Technical data

Rated power input: 250 W

Orbital stroke rate when idling: 14.000 / 24.000 1/min

Oscillating circuit diameter: 2,0 mm

Weight: 1,6 kg





PSS 300 AE

Sanding surface

Sanding plate, width: 115 mm

Sanding plate, length: 230 mm

Sanding surface: 265 cm²

Sanding sheet for clamping, width: 115 mm

Sanding sheet for clamping, length: 280 mm

Sanding sheet with Velcro-type fastening, width: 115 mm

Sanding sheet with Velcro-type fastening, length: 230 mm

Technical data

Rated power input: 250 W

No-load speed: 7.000 / 12.000 1/min

Orbital stroke rate when idling: 14.000 / 24.000 1/min

Power output: 125 W

Oscillating circuit diameter: 1,8 mm

Weight: 1,9 kg



PSS 240 AE

Sanding surface

Sanding plate, width: 92 mm

Sanding plate, length: 182 mm

Sanding surface: 167 cm²

Sanding sheet for clamping, width: 93 mm

Sanding sheet for clamping, length: 230 mm

Technical data

Rated power input: 240 W

Power output: 100 W

Oscillating circuit diameter: 1,8 mm

Weight: 1,6 kg

PSS 240 A

Sanding surface

Sanding plate, width: 92 mm

Sanding plate, length: 182 mm

Sanding surface: 167 cm²

Sanding sheet for clamping, width: 93 mm

Sanding sheet for clamping, length: 230 mm

Technical data

Rated power input: 240 W

Orbital stroke rate when idling: 19.000 / 27.000 1/min

Power output: 100 W

Oscillating circuit diameter: 1,8 mm

Weight: 1,6 kg



PSS 180 A

Sanding surface

Sanding plate, width: 92 mm

Sanding plate, length: 182 mm

Sanding surface: 167 cm²

Sanding sheet for clamping, width: 93 mm

Sanding sheet for clamping, length: 230 mm

Technical data

Rated power input: 180 W

Orbital stroke rate when idling: 24.000 1/min

Power output: 75 W

Oscillating circuit diameter: 1,8 mm

Weight: 1,5 kg





PSS 28 AE

Sanding surface

Sanding plate, width: 114 mm

Sanding plate, length: 227 mm

Sanding surface: 260 cm²

Sanding sheet for clamping, width: 115 mm

Sanding sheet for clamping, length: 280 mm

Technical data

Rated power input: 250 W

No-load speed: 14.000 / 20.000 1/min

Power output: 110 W

Oscillating circuit diameter: 2,4 mm

Weight: 2,0 kg