



## G-2702A Hot water cleaner

The 2000 series machines are constructed with minimal main components, making them extremely easy to maintain and operate.

Gerni's fully integrated boiler, coil and water tank provides

- reliable, effective and versatile performance
- pre-heating of water
- upright design
- automatic start/stop
- flame control as standard
- can be wall-mounted
- low fuel consumption
- low fuel and water cut-out
- Turbo Laser as standard

10 m long hose, providing a wide working radius.

Pistol has built-in automatic start/stop function.

Rustproof water-cooled boiler



### Technical overview G-2702A

|   |                    |
|---|--------------------|
| <b>Pump Pressure (BAR/PSI)</b>                    | <b>155/2103</b>    |
| <b>Turbo pressure (ETP-BAR/ETP-PSI)</b>           | <b>195/2828</b>    |
| <b>Water quantity ( l/h )</b>                     | <b>720</b>         |
| <b>Phases</b>                                     | <b>3</b>           |
| <b>Voltage ( V )</b>                              | <b>230</b>         |
| <b>Frequency Hz</b>                               | <b>50 / 60</b>     |
| <b>Amp. consumption ( A )</b>                     | <b>10.5</b>        |
| <b>Power consumption ( kW )</b>                   | <b>3.5</b>         |
| <b>Fuel consumption l/h ( delta t = 50 gr C )</b> | <b>2.85</b>        |
| <b>Max. temp. v. max. flow ( deg. C )</b>         | <b>80</b>          |
| <b>Weight ( kg )</b>                              | <b>73</b>          |
| <b>Dimension H x W x L (mm)</b>                   | <b>535x585x780</b> |