

DH50MB

SDS-max Rotary Demolition Hammer

Variable speed/Two mode action/Safety clutch

Capacity: Concrete - Drill bit 50mm
Concrete - TCT Core bit 160mm

Bit Shank SDS-max
Power Input 1400W
No-load Speed 120-250/min
Full Load Impact Rate 1200-2500/min
Impact Energy 5.0-18.0J
Overall Length 495mm
Weight 9.8kg

Standard Accessories: 3 hex wrenches, side handle, depth stop, grease pack, carrying case.



H45MR SDS-max Demolition Hammer

Soft grip handle

Power Input 950W
Full Load Impact Rate 3000/min
Impact Energy 12.5J
Bit Shank SDS-max
Overall Length 454mm
Weight 5.9kg

Standard Accessories: 3 hex bar wrenches, side handle assy, bull point, carrying case.



H60MB SDS-max Demolition Hammer

Variable speed/Electronic speed control

Power Input 1300W
Full Load Impact Rate 900-1600/min
Impact Energy 6.0-25.0J
Bit Shank SDS-max
Overall Length 576mm
Weight 10.5kg

Standard Accessories: wrench, side handle, bull point, carrying case.

H25PV SDS-Plus Demolition Hammer

Push fit bit lock/Variable speed

Power Input 500W
Full Load Impact Rate 0-3200/min
Impact Energy 0-4.0J
Bit Shank SDS-Plus
Overall Length 320mm
Weight 3.2kg
Standard Accessories: Carrying case.



H60KA Demolition Hammer

Power Input 1300W
Full Load Impact Rate 1600/min
Impact Energy 25.0J
Bit Shank K-Hex
Overall Length 570mm
Weight 11kg

Standard Accessories: bull point, side handle, hex wrench, dust cover, steel carrying case.



H65SD2 Heavy Duty Breaker

Auto stop carbon brushes

Power Input 1240W
Full Load Impact Rate 1400/min
Impact Energy 42.0J
Bit Shank 28mm Hex
Overall Length 823mm
Weight 18.0kg

Standard Accessories: 2 wrenches, carrying case.

NEW



The H65SD2 and H70SD accept 3 types of 28mm hex shank:

- Air tool shank bit
- Standard hex shank bit (combo type)
- Retaining groove bit without collar

H70SD Heavy Duty Breaker

Power input 1240W
Full Load Impact Rate 1400/min
Impact energy 42.0J
Overall Height 722mm
Weight 20.0kg
Standard Accessories: 2 wrenches

