

# IBIX SANDBLASTING EQUIPMENT



Sabbiatrice



Spazzola per sabbicare senza produrre polvere



Zainetto porta sabbiatrice

## IBIX 9

### TECHNICAL SPECIFICATION

- Air pressure: from 0.5 to 7 bar
  - Air consumption: from 250 ltr/min
  - standard nozzle 3mm (1.5-2-2.5-3.5-4-4.5mm cylindrical nozzles or 2.5-4-5.6 Venturi nozzles: Optional)
  - Abrasive/inert material particle size: up to 1.2mm
  - Standard blasting hose length: 3m. Other lengths available on request (recommended max length 10m)
  - Abrasive tank capacity: 8.7 ltr
  - Height: 850mm
  - Width: 450mm
  - Weight (with tank empty): 12kg approx.
  - Backpack-type sandblast carrier
  - Suction for dust-free sandblasting
- 
- Portable: equipped with wheels, a carry handle and lightweight, the IBIX sandblaster can be transported and manoeuvred with ease
  - Low air consumption
  - User Friendly
  - Vast range of applications
  - Easy to fill tank
  - Easy adjustment of the abrasive/inert material-air-ratio
  - Precision sandblasting provided by a vast range of nozzles
  - Versatile, multi-role performance: operates with any type of inert material
    - abrasive minerals (e.g. GARNET in all particle sizes from 20-40 to 350 Mesh)
    - aluminium oxide
    - glass or ceramic beads
    - sodium bicarbonate and calcium carbonate
    - olivine
    - quartz
    - Safety: the machine complies with the standards in force

## ADVANTAGES