

CE NO. Z95-533-255-A

## 150mm

### TAH-101

|                               |                      |
|-------------------------------|----------------------|
| Chisel Shank(in)              | 0.401                |
| Bore Diameter (ID)            | 3/4"(19.05mm)        |
| Stroke Length                 | 1-5/8"(41mm)         |
| Bolw per Min (BPM)            | 4,500                |
| Sound Level dB (A)            | 101                  |
| Vibration (m/s <sup>2</sup> ) | 19.3                 |
| Air Pressure (PSI)            | 90PSI                |
| Air Inlet (NPT)               | 1/4"                 |
| Avg. Air Cons. (CFM)          | 5                    |
| Packing (pcs/N.W./G.W./cuft)  | 10/16Kgs/17Kgs/0.61' |

## 190mm

### TAH-106



|                               |                      |
|-------------------------------|----------------------|
| Chisel Shank(in)              | 0.401                |
| Bore Diameter (ID)            | 3/4"(19.05mm)        |
| Stroke Length                 | 2-5/8"(66mm)         |
| Bolw per Min (BPM)            | 3,000                |
| Sound Level dB (A)            | 99                   |
| Vibration (m/s <sup>2</sup> ) | 4.0                  |
| Air Pressure (PSI)            | 90PSI                |
| Air Inlet (NPT)               | 1/4"                 |
| Avg. Air Cons. (CFM)          | 5.5                  |
| Packing (pcs/N.W./G.W./cuft)  | 10/17Kgs/18Kgs/0.67' |

## 190mm

### TAH-111



|                               |                     |
|-------------------------------|---------------------|
| Chisel Shank(in)              | 0.401               |
| Bore Diameter (ID)            | 3/4"(19.05mm)       |
| Stroke Length                 | 2-5/8"(66mm)        |
| Bolw per Min (BPM)            | 3,000               |
| Sound Level dB (A)            | 99                  |
| Vibration (m/s <sup>2</sup> ) | 7.0                 |
| Air Pressure (PSI)            | 90PSI               |
| Air Inlet (NPT)               | 1/4"                |
| Avg. Air Cons. (CFM)          | 6                   |
| Packing (pcs/N.W./G.W./cuft)  | 10/20Kgs/22Kgs/0.8' |

## 250mm Heavy Dury

### TAH-112



|                               |                        |
|-------------------------------|------------------------|
| Chisel Shank(in)              | 0.401                  |
| Bore Diameter (ID)            | 3/4"(19.05mm)          |
| Stroke Length                 | 3-5/8"(92mm)           |
| Bolw per Min (BPM)            | 2,200                  |
| Sound Level dB (A)            | 101                    |
| Vibration (m/s <sup>2</sup> ) | 92                     |
| Air Pressure (PSI)            | 90PSI                  |
| Air Inlet (NPT)               | 1/4"                   |
| Avg. Air Cons. (CFM)          | 6                      |
| Packing (pcs/N.W./G.W./cuft)  | 10/22.5Kgs/25Kgs/1.06' |

