

Grinders

Angle models



G-50EF

Type	Brand	Wheel size mm	Rotations p/min	Power kW	Spindle (whitworth)	Air-consumption l/sec	Weight kg	Inlet thread	Hose diam. mm
TAG-400 QJL	TOKU	100 x 6 x 16	13.000	0.55	*	10.8	1.70	PT 3/8"	10
RRG-234	RRA	100 x 6 x 16	12.500	0.45	3/8 UNF	11.0	1.55	PT 1/4"	10
HS-4G	YOKOTA	100 x 6 x 16	12.000	0.48	M12 x 1,25	9.2	1.40	PT 1/4"	10
G-40SRF	YOKOTA	100 x 6 x 16	13.000	0.39	M8 x 1.25	7.5	0.90	PT 1/4"	6.5
G-40EF	YOKOTA	115 x 6 x 22	13.000	0.60	7/16"	10.8	1.40	PT 1/4"	10
G-40RF	YOKOTA	115 x 6 x 22	13.000	0.60	7/16"	10.8	1.30	PT 1/4"	10
TAG-450 QJL	TOKU	115 x 6 x 22	13.000	0.55	*	10.8	1.80	PT 3/8"	10
RRG-244	RRA	115 x 6 x 22	12.500	0.45	3/8 UNF	11.0	1.60	PT 1/4"	10
G-50EF	YOKOTA	125 x 6 x 22	12.000	0.60	7/16"	10.8	1.50	PT 1/4"	10
G-50RF	YOKOTA	125 x 6 x 22	12.000	0.60	7/16"	10.8	1.40	PT 1/4"	10
TAG-500 QJL	TOKU	125 x 6 x 22	12.000	0.55	*	10.8	1.80	PT 3/8"	10
RRG-255	RRA	125 x 6 x 22	12.000	0.45	3/8 UNF	11.0	1.60	PT 1/4"	10
G-70EF	YOKOTA	180 x 6 x 22	8.500	1.12	5/8"	16.7	2.90	PT 3/8"	13
TAG-700 QJL	TOKU	180 x 6 x 22	8.500	1.10	*	16.6	3.10	PT 3/8"	13
TAG-900 QJL	TOKU	230 x 6 x 22	6.500	1.10	*	16.6	3.10	PT 3/8"	13

EF = safety trigger (all other grinders have a safety lever).

* = see adaptor page 67.

All angle grinders are supplied with side handle, with exception of model G-40SRF.

Flanges for cup wheels and a tool service set for mounting the flanges are supplied with all grinders.